

i-SENSYS X C1127i Series

ENHANCE YOUR FLEET OF DOCUMENT WORKFLOW SOLUTIONS

High quality, compact A4 colour multifunction printers with cloud connectivity













i-SENSYS X C1127i Series

(M) PRODUCTIVITY

- · Large, responsive touchscreen display
- Easy customisation of device functions
- Double-sided printing as standard
- One Pass Scan for fast digitisation of paper documents

SECURITY

- Verify System at Start-up protects device functionality
- User Authentication secures device access
- Secure Print function prevents unauthorised viewing of printed material
- · Scan and send documents securely with optional Encrypted PDF mode

(A) CONNECTIVITY

- Remote device set-up and control with the Canon Print Business App
- · Compatible with Mopria, Apple Air Print and Google Cloud Print
- Near field communication (NFC) support (C1127iF only)

(COMPACT DESIGN

- Solve cost and space limitations
- · Compact devices feature an all-in-one toner cartridge
- · Flexible configuration integrates into any office environment
- Easy access to replace consumables

CONTROL AND MAINTENANCE

- · Remote diagnostics and assistance help minimise downtime
- · Cloud and server-based software options centralise fleet control
- · Access printer control functions via PC or mobile devices
- Easy toner replacement

QUICK FACTS

i-SENSYS X C1127i

- Print, Copy, Scan and Send
- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 27ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- · Scan speed: up to 47ipm
- Network, Wi-Fi, USB and QR code connectivity
- Max paper input capacity: 900 sheets

i-SENSYS X C1127iF

- · Print, Copy, Scan, Send and Fax
- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 27ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- Scan speed: up to 47ipm
- Network, Wi-Fi, USB, QR code and NFC
- Max paper input capacity: 900 sheets

SERVICES

CORE

Perform routine office operations safely and with ease, utilising embedded software including uniFLOW Online Express and other available services offering complete device maintenance and support





HARDWARE

SERVICES

BESPOKE

Choose a tailored service to suit your business needs by removing unnecessary print management burdens. Consult with Canon experts about your specific requirements to find a fitting Print Managed Services option

ENHANCED

Expand cloud capabilities with uniFLOW Online, Canon's all-in-one print management system



TECHNICAL SPECIFICATIONS

i-SENSYS X C1127i Series

Machine type Available functions

Colour Laser All-In-One

PRINTER

Print speed

Printing method Print resolution Warm-up time First Print Out Time

Printer languages

Fonts

Print margins

Toner saver mode Advanced printing features

i-SENSYS X C1127iF: Print, Copy, Scan and Fax i-SENSYS X C1127i: Print, Copy, Scan

Single sided : Up to 27 ppm (A4) Up to 49 ppm(A5-Landscape) Double sided : Up to 24.5 ipm (A4) Colour laser beam printing

1200 x 1200 dpi

Approx. 13 seconds or less from power on Colour approx.: 8.6 seconds or less Mono approx.: 7.7 seconds or less UFRII, PCL 5c1, PCL6, Adobe® PostScript3

93 PCL fonts 136 PostScript fonts

5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)

Yes

i-SENSY X C1127iE:

ADF (A4):

i-SENSY X C1127iF:
Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Barcode Print²
Touch & Print (NFC)
Google Cloud Print Ready
iOS: AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon Print Service
Plug-in, Canon PRINT Business app
i-SENSYS X C1127i:
Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Barcode Print²
Google Cloud Print Ready
iOS: AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon Print Service
Plug-in, Canon PRINT Business app

Single sided (A4): Up to 27 ppm Double sided (A4): Up to 21.9 ipm

Colour Approx. 12.0 seconds or less Mono Approx. 10.2 seconds or less Platen (A4): Colour Approx. 11.3 seconds or less

Text/Photo/Map (Default),Text/Photo/Map (quality), Printed Image, Text

Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy

Mono Approx, 9.8 seconds or less

2-sided to 2-sided (Automatic)

Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi

24 bit/24 bit (input/output)

Single sided mono: 27ipm (300x600dpi) Single sided colour: 14ipm (300x600dpi) Double sided mono: 47ipm (300x600dpi) Double sided colour: 27ipm (300x600dpi)

TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF³/PDF (Digital signature)³

TIFF/JPEG/PDF/Compact PDF/Searchable PDF/Encrypted PDF³/PDF (Digital signature)³

TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF³/PDF (Digital signature)³

TIFF/JPEG/PDF/Compact PDF/Searchable PDF/Encrypted PDF³/PDF (Digital signature)³

25-400% in 1% increments

Up to 600 x 600 dpi

Up to 999 copies

Colour

256 levels

216mm

TWAIN, WIA, ICA

COPIER

Copy speed

First Copy Output Time (FCOT)

Copy resolution Copy modes

Double sided copying

Multiple copy

Reduction / Enlargement

Other features

SCANNER

Туре

Scan resolution

Scan speed

Colour scanning depth Grevscales

Compatibility Max. scan width

Scan to E-mail

Scan to PC

Scan to USB memory key

Scan to FTP

Scan to Cloud

iFAX

FAX

Modem speed Receive mode

Fax resolution

i-SENSYS X C1127iF only 33.6 Kbps (Up to 3 seconds/page⁵)

TIFF/JPEG/PDF/PNG4

Fax only, Fax/Tel Auto Switch, Answer Mode, Manual

ITU-T.37

Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi

FAX memory

Speed dials

Group dials/destinations Sequential broadcast Memory backup

Double sided faxing Other features

MEDIA HANDLING Scanner type Paper input (Standard)

Paper input (Option) Paper output Media types

Media sizes

Up to 512 pages⁵ Up to 281 dials

Max. 299 dials / Max. 299 destinations

Max. 310 destinations

Permanent fax memory backup (Backup with flash memory) Yes (Transmit and Receive)

Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports

Platen 2-sided ADE (single pass)

250-sheet cassette 50-sheet multi-purpose tray 50-sheet ADF

550-sheet cassette

150-sheet

Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Label, Post card, Envelope

Cassette (Standard):

Cassette (Standard): A4, A5, A5 (Landscape), B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Envelop (COM10, DL, C5), Custom sizes: Min. 100 x 148 mm Max. 216.0 x 355.6 mm.

Multi-purpose tray:
A4, A5, A5 (Landscape), B5, Legal, Letter,
Executive, Statement, OFFICIO, B-OFFICIO,
M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card,
Indexcard, Envelope (COM10, DL, C5, Monarch),
Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6

Cassette (Optional):
A4, A5, B5, Legal, Letter, Executive, Statement,
OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL,
Foolscap, 16K, Post card, Envelop (COM10, DL, C5),
Custom sizes:
Min. 100 x 148 mm Max. 216.0 x 355.6 mm.

A4, A5, B5, Legal, Letter, Statement, Custom sizes: Min. 128 x 139.7 mm Max 215.9 x 355.6 mm

Cassette (standard and optional): 60 to 163 g/m² (Up to 200 g/m² with Coated paper) Multi-purpose tray: 60 to 176 g/m² (Up to 200 g/m² with Coated paper) ADF: 50 to 105 g/m²

Automatic

Double sided printing

Cassette: A4, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K Custom size - Min. 176 x 250 mm Max. 215.9 x 355.6

60 to 200 g/m²

INTERFACE & SOFTWARE Interface type

Media weights

Operating System compatibility

Network Protocol

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Windows* 10 / Windows* 8.1 / Windows* 7 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server* 2008 /Mac OS X version 10.9.5 & up / Mac OS 10.15 & up Linux⁶

LPD, RAW, WSD-Print (IPv4,IPv6)

Email, SMB, WSD-Scan(IPv4, IPv6), FTP-Scan, iFAX

Email, SMB, WSD-Scan(IPV4, IPV6), F1P-Scan, IFA
TCP/IP Application Services:
Bonjour(mDNS), HTTP, HTTPS, POP before SMTP
(IPV4,IPV6)
DHCP, ARP+PING, Auto IP, WINS (IPV4)
DHCPV6 (IPV6)

Management: SNMPv1, SNMPv3 (IPv4,IPv6)

SNMPVI, SNMPV3 (IPV4,IPV6)
Security (wired):
IP/Mac address filtering, IEEE802.1X, SNMPv3,
SSL (HTTPS, IPPS)
Security (wireless):
Infrastructure Mode:
WEP(64/128 bit), WPA-PSK(TKIP/AES),
WPA2-PSK(TKIP/AES)

Access Point Mode: WPA2-PSK(AES)



TECHNICAL SPECIFICATIONS

i-SENSYS X C1127i Series

Software and printer management

MF Scan Utility,
Remote User Interface (RUI),
Department ID Management,
Toner Status Tool,
iW Enterprise Management Console Server-based
software for centralised management of a fleet of
devices

eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture automatic consumables management and remote

diagnostics.
Universal Log-in Manager / uniFLOW online / uniFLOW online Express / uniFLOW Compatibility Application Library

GENERAL FEATURES

Recommended Monthly Print Volume

Duty cycle **Processor Speed** Memory Control panel

Dimensions with trays $(W \times D \times H)$

Installation space $(W \times D \times H)$

Weight Operating environment

Power Source Power Consumption 750 - 4.000 pages per month

Max. 50,000 pages per month⁷

800MHz x 2 1GB

12.7 cm LCD Colour Touch Screen 471 mm x 469 mm x 460 mm

671 mm x 1.312 mm x 966 mm

Approx. 24.5 Kg

Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)

220-240V(±10%) 50/60Hz (±2Hz)

Z2U-Z4UV(E10%) 5U/60HZ (±2Hz)

Maximum: Approx. 1,390 W
Active printing: Approx. 550W
Standby: Approx. 18.0 W
Sleep mode: Approx. 0.7 W
Typical Electricity Consumption (TEC): 0.31 kWh/week¹⁰
For detailed information relating to Lot26
regulation, please go to: http://www.canoneurope.com/

europe.com/ For_Work/Lot26/index.aspx

Noise Levels

Sound Pressure⁸: i-SENSYS X C1127iF Active: Simplex 48 dB / Duplex 49 dB

Standby: 26 dB i-SENSYS X C1127i Active: Simplex 48 Standby: 28 dB 48 dB / Duplex 50 dB

Sound Power[®]: i-SENSYS X C1127iF Active: Simplex 62 dB or less / Duplex 63 dB or less Standby: 42dB or less i-SENSYS X C1127i Active: Simplex 63dB or less / Duplex 64 dB or less Standby: 42dB or less

CONSUMARIES

Cartridges

TONER T09 Black (7,600 pages°) TONER T09 Cyan (5,900 pages°) TONER T09 Magenta (5,900 pages°) TONER T09 Yellow (5,900 pages°)

ACCESSORIES/ OPTIONS

i-SENSYS X C1127iF:
CST.Feeding Module-AF1 (550-sheet cassette)
TEL 6 Kit Long Cord (Telephone handset)
Barcode Printing Kit-E1E
MiCard Multi (Card reader for identification with
RFID or magnetic cards with uniFLOW)
Micard Plus (Card reader for identification with
RFID or magnetic cards with uniFLOW)
MiCard Attachment Kit-B1
Send PDF Security Feature Set-E1

i-SENSYS X C1127i

i-SENSYS X C1127i: CST.Feeding Module-AF1 (550-sheet cassette) Barcode Printing Kit-E1E MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW) MiCard Attachment Kit-B1 Send PDF Security Feature Set-E1

Notes:

- Commands supported only. Third party driver or direct printing from application required
- Accessory Barcode Printing Kit-E1E is required
- Accessory Send PDF Security Feature Set-E1 is required Scan by MF Scan Utility or Canon PRINT Business app
- Based on ITU-T Standard Chart No. 1
- Web distribution only. Linux support printing only. [7]
- Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
- Declared noise emission in accordance with ISO 9296
- Based on ISO/IEC 19798
- [10] As per US ENERGY STAR* version3.0.

Software & Solutions









Compatibility









Canon Ireland

3006 Lake Drive Citywest, Saggart Co. Dublin, Ireland

Telephone No: 01 2052400 Facsimile No: 01 2052525

canon.ie

Canon (UK) Ltd

5 The Square Stockley Park Uxbridge

UB111ET Tel: 01895 648 000

www.canon.co.uk

Canon Inc. canon.com Canon Europe

canon-europe.com English edition © Canon Europa N.V.,2020

