Simple yet smart A4 Multifunctional printers ideal for small businesses with flexible workers.

Easily achieve professionalquality results from the smart, simple and compact MF410 series black and white laser Multifunctional printers that offer print, copy, scan and fax* plus support for mobile devices.



- Offering professional-quality printing at speeds of up to 33ppm
- Versatile enough to handle all your document needs despite its impressively compact size.
- An intuitive 3.5" colour touch screen
- 300 (MF411dw and MF416dw) or 550-page (MF418x and MF419x) paper capacity to work without interruption.
- Quick First-Print from start-up all help your teams to work more efficiently
- Secure Print function protects your documents with a PIN code, even when you're printing from a mobile device.

Flexible working

- Support for Apple AirPrint (iOS) and Mopria (Android), your workgroup can print from any enabled device.
- Access a wide range of advanced features with the Canon PRINT Business mobile app.
- Connect the device to a Google Cloud Print account in seconds.
- With NFC Touch & Print users can experience near-instant printing from compatible mobile devices by simply tapping it on the printer's NFC mark (only available on the MF416dw).

Enhanced document sharing

 Connect seamlessly between the devices and popular cloud storage services like Evernote* and DropBox

Canon

 Capture, digitise and share documents on the go - or simply to scan and email in a single operation.

Smart networking capabilities

- · Flexible networking capabilities
- · WiFi and Ethernet connectivity
- Support for PCL5e/6 and Adobe PostScript printer languages, enable hassle-free integration into managed network environments.
- With Canon's e-Maintenance remote service management and support for Canon's uniFLOW*(only available on MF418x and MF419x) output management system make the MF410 series equally well-suited to managed print services environments.

Simple and sustainable ownership

- Consistent reliability and renewed quality are ensured every time you change your toner thanks to the Canon All-In-One Cartridge design that replaces all key components at once.
- Low energy consumption in Sleep and Standby modes
- Automatic duplex printing to reduce waste
- Smart power-saving Auto Off feature















i-SENSYS / MF411dw MF416dw MF418x MF419x

Optional Accessories

Paper Feeder Unit- PF44 (Available on MF411dw and MF416dw)

 Additional 500 sheet paper cassette, 1 unit can be added to the main unit.

Cassette Feeding Unit- U1 (Available on MF418x and MF419x)

 Additional 500 sheet paper cassette, 1 unit can be added to the main unit.

Plain Pedestal Type- K1

• Place under the device to increase height when free standing

MiCard Attachment- B1 (Available on MF418x and MF419x)

 Required to attach NTware products MiCard PLUS or Mi Card Multi to the device.

Barcode Print Kit- E1 (Available on MF418x and MF419x)

 Installs bar code fonts for bar code printing. This kit, which is delivered boxed, includes a license access certificate for activation.

Barcode Print Kit- E1E (Available on MF418x and MF419x)

 Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation.

TEL 6 Kit Long Cord

• Optional handset for fax function.

Copy Card Reader- F1 (Available on MF418x and MF419x)

 The card control system simplifies the logon process of Department ID Management.

Copy Card Reader Attachment- J1 (Available on MF418x and MF419x)

• This kit is required when attaching the copy card reader and comprises of components to attach the products.

Control I/F Kit- C1 (Available on MF418x and MF419x)

 This kit is required to attach 3rd party card readers or coin vendor machines to the device.

i-SENSYS MF411dw and MF416dw



Main Unit Main unit + 1
Paper Feeder

Main unit + 1 Paper Feeder Unit- PF44

i-SENSYS MF418x and MF419x



Main Unit

Main unit + 1 Cassette Feeding Unit- U1



Technical Specifications

I-SENSYS / MF411dw MF416dw MF418x MF419x

Machine type Available functions Mono Laser All-In-One

Print, Copy, Scan and Fax* (*MF416dw, MF419x)

Print speed

Printing method

Print quality Print resolution First Print Out Time

Double sided printing

Printer languages Fonts

Print margins

Toner saver mode

Advanced printing features

Copier Copy speed

First Copy Output Time (FCOT)

Copy resolution Copy modes Double sided copying

Multiple copy Reduction / Enlargement

Other features

Type Scan resolution

Scan speed

Colour scanning depth

Greyscales Compatibility Max. scan width Scan to E-mail

Scan to PC Scan to USB memory key

Scan to FTP Scan to Cloud iFAX

Fax (MF416dw, MF419x)

Modem speed

Receive mode

Fax resolution

FAX memory Speed dials

Group dials/destinations Sequential broadcast

Memory backup Double sided faxing

Media handling

Other features

Scanner type Paper input (Standard)

Paper input (Option) Paper output

Media types

Media sizes

Media weights

Single sided: Up to 33 ppm (A4) Double sided: Up to 16.8 ipm (A4) Monochrome laser beam printing

Up to 1200 x 1200 dpi 600 x 600 dpi Approx: 6.3 seconds or less

Automatic UFRII. PCL5e¹. PCL6. Adobe PostScript

45/93 PCL fonts 136 PostScript fonts

5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)

res
Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Google Cloud Print Ready
IOS. Air/Print, Canon PRINT Business app
Android; Mopria certified, Canon Print Service Plug-in,
Canon PRINT Business app

Single sided: Up to 33 ppm (A4) Double sided: Up to 16.8 ipm (A4)

Approx. 10 seconds or less Up to 600 x 600 dpi

Text/Photo, Text/Photo (quality), Photo, Text

2-sided to 2-sided (Automatic)

25-400% in 1% increments

Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy

Colour

Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi Single sided mono: 33ipm (300x300dpi) Single sided colour: 11ipm (300x300dpi) Double sided mono: 13ipm (300x300dpi) Double sided colour: 7ipm (300x300dpi) 24 bit/24 bit (input/output)

256 levels TWAIN, WIA

TIFF/JPEG/PDF/Compact PDF/Searchable PDF TIFF/JPEG/PDF/Compact PDF/Searchable PDF TIFF/JPEG/PDF/Compact PDF/Searchable PDF TIFF/JPEG/PDF/Compact PDF/Searchable PDF TIFF/JPEG/PDF/PNG²

ITU-T.37 (MF416dw, MF419x)

33.6 Kbps (Up to 3 seconds/page³)

Fax only, Fax/Tel Auto Switch, Answer Mode, Manual

Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi

Up to 512 pages³ Up to 281 dials

Max. 199 dials / Max. 199 destinations Max. 310 destinations

Permanent fax memory backup (Backup with flash memory)

Yes (Transmit and Receive)

Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports,

Fax Activity Result Reports, Fax Activity Management Reports

Flatbed and Automatic Document Feeder (DADF)

250-sheet cassette (MF411dw, MF416dw) 500-sheet cassette (MF418x, MF419x) 50-sheet multi-purpose tray 50-sheet DADF

500-sheet cassette 150-sheet

Plain paper, Recycled paper, Heavy Paper, Label, Postcard, Envelope

A4, A5, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Custom sizes: Min. 105 x 148 mm Max. 215.9 x 355.6 mm.

Multi-purpose tray:
A4, A5, B5, Legal, Letter, Executive, Statement, OFFICIO,
B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card,
Index.card, Envelope (COMIO, Monarch, DL, C5),
Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm.

A4, A5, B5, B6, Legal, Letter, Statement, Custom sizes (W x L): Min. 128 x 139.7 mm Max 215.9 x 355.6 mm

Cassette: 60 to 128 g/m² (optional and standard) Multi-purpose tray: 60 to 163 g/m² ADF: 50 to 105 g/m²

Interface & Software

Interface type

Network Protocol

Operating System compatibility

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.1lb/g/n, Wireless Direct Connection Windows* 10 / Windows* 8.1 / Windows* 8 / Windows* 7 / Server* 2012R2* / Server* 2012* / Server* 2008R2* / Server* 2008R2* / Server* 2008A2* / Serv

I PD. RAW. WSD-Print (IPv4.IPv6)

Scan: Email, SMB, WSD-Scan(IPv4, IPv6)

TCP/IP Application Services:
Bonjour(mDNS), HTTP, HTTPS, POP before SMTP (IPv4,IPv6)
DHCP, ARP+PING, Auto IP, WINS (IPv4)
DHCPv6 (IPv6)

Management: SNMPv1, SNMPv3 (IPv4,IPv6)

Security (wired): IP/Mac address filtering, IEEE802.1X, SNMPv3, HTTPS, IPsec

Security (wireless): WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(AES)

WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(AES)
Prestol Page Manager,
MF Scan Utility,
Remote User Interface (RUI),
SSID Tool,
Department ID Management,
Toner Status Tool,
W Management Console: Server-based software for centralised
management of a fleet of devices
eMaintenance: embedded RDS allows remote eMaintenance
services such as meter capture, automatic consumables
management and remote diagnostics.

Recommended Monthly Print Volume

Duty cycle Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight

Operating environment

Power Source

Noise Levels

Consumables Cartridges

Accessories/Options Items

750 - 3,000 pages per month (MF411dw, MF416dw) 1,000 - 5,000 pages per month (MF418x, MF419x)

Max. 50,000 pages per month ⁶

8.9 cm LCD Colour Touch Screen

390 mm x 473 mm x 431 mm (MF411dw, MF416dw) 450 mm x 472 mm x 465 mm (MF418x, MF419x) 590 mm x 1,182 mm x 795 mm (MF411dw, MF416dw) 650 mm x 1,181 mm x 827 mm (MF418x, MF419x) Approx. 19 Kg (MF411dw, MF416dw) Approx. 21,4 Kg (MF418x, MF419x)

Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V(±10%) 50/60Hz (±2Hz)

220-240V(±10%) 50/60Hz (±2Hz)

Maximum: Approx. 1160 W

Standby: Approx. 1160 W

MKH418x, MF419x)

Sleep mode: Approx. 1.4 W7

Power switch off: 0.1W or less

Typical Electricity Consumption (TEC): 1.2 kWh/week (230V)

Idle time required to enter sleep mode: 3-60 min (default: 3 min)

Idle time required to enter Auto Shutdown: 4 hours (default)

Sound Pressure⁸: Active: 53 dB in B/W printing Standby: Inaudible

Sound Power⁸: Active: 70.6 dB or less in B/W printing Standby: 53 dB or less (Seine 2 and 4 52dB)

Cartridge 719 (2,100 pages⁹)¹⁰ Cartridge 719H (6,400 pages⁹)¹⁰

PAPER FEEDER PF-44 - 500-sheet cassette

PAPER FEEDER PF-44 - 500-sheet cassette
(MF41Idw, MF416dw)
CASSETTE FEEDING UNIT-U1 - 500-sheet cassette
(MF41Bx, MF419x)
TEL 6 kIT - Telephone handset (MF416dw, MF419x)
BARCODE PRINTING KIT-E1 (MF418x, MF419x)
BARCODE PRINTING KIT-E1E (MF418x, MF419x)
COPY CARD READER-F1 - Physical card access system that
limits access to authorised users (MF418x, MF419x)
COPY CARD READER ATTACHMENT-J1 (MF418x, MF419x)
MiCard Multi - Card reader for identification with RFID or
magnetic cards with uniFLOW (MF418x, MF419x)
MiCard Plus - Card reader for identification with RFID or
magnetic cards with uniFLOW (MF418x, MF419x)
MiCard Attachment Kit-A2 (MF418x, MF419x)
COPY CONTROL INTERFACE KIT-C1 - Allows connection
(CCVI | F) between 3" Party copy control terminal and MFPs for
cost recovery use (MF418x, MF419x)
PLAIN PEDESTAL TYPE-K1 (MF418x, MF419x)

(1) Commands supported only. Third party driver or direct printing from application required

[2] Scan by MF Scan Utility or Canon PRINT Business app

[3] Based on ITU-T Standard Chart No. 1

[4] Network scanning not supported [5] Web distribution only. Linux support printing only.

[6] Duty cycle is defined as the maximum number of printed pages for a single peak month.

Any usage above the recommended duty cycle may decrease the life of the product ⁽⁷⁾ When in wireless mode, consumption will be 2.1W

[8] Declared noise emission in accordance with ISO 9296 [9] Based on ISO/IEC 19798

[10] Printer ships with 2,100 pages cartridge


Canon Inc. canon.com Canon Europe canon-europe.com **English** edition © Canon Europa N.V.,2016



i-SENSYS MF411dw MF416dw MF418x MF419x

Simple yet smart A4 Multifunctional printers ideal for small businesses with flexible workers.

Easily achieve professional-quality results from the smart, simple and compact MF410 series black and white laser Multifunctional printers that offer print, copy, scan



Sales Start Date: June, 2016

Product Details:

Product Name	Mercury Code	EAN Code
i-SENSYS MF411dw	0291C022AA	4549292031874
i-SENSYS MF416dw	0291C013AA	4549292031751
i-SENSYS MF418x	0291C008AA	4549292031690
i-SENSYS MF419x	0291C002AA	4549292031621

Optional Accessories:

Product Name	Mercury Code	EAN Code
Cassette Feeding Unit- U1	0732A023AA	4960999635620
Paper Feeder PF-44	3439B001AA	4960999630540
Telephone 6 Kit UK (CW)	0752A053AA	4960999453897
Telephone 6 Kit EU (CW)	0752A054AA	4960999453910
Telephone 6 Kit SA (CW)	0752A055AA	4960999453927
Copy Card Reader-F1	4784B001AA	4960999679686
Copy Card Reader Attachment-G1	5140B001AA	4960999689920
MiCard Attachment Kit-A2	5146B003AA	4549292037081
Copy Contol I/F Kit-C1	5145B001AA	4960999780269
Barcode Printing Kit-E1	5143B001AA	4960999689951
Barcode Printing Kit-E1E EU	5143B002AA	N/A (e-delivery)
Plain Pedestal Type-K1	6132B001AA	4960999841267

Consumables:

Product Name	Mercury Code	EAN Code
Cartridge 719	3479B002AB	4960999650289
Cartridge 719H	3479B002AB	4960999650319

Measurement / Logistic Information:

Product Name	Mercury code	Package Style	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
	0291C002AA	Вох	1	590	565	578	27
	0291C008AA	Pallet	8	1180	1130	1156	217
		Container 40ft HCD	320	-	-	-	-
i-SENSYS MF416dw i-SENSYS MF411dw	0291C013AA 0291C022AA	Box	1	566	503	545	23
		Pallet	8	1132	1006	1090	185
		Container 40ft HCD	352	-	-	-	-

What's in the box?

- Main unit
- Canon Cartridge 719 starter
- Power supply cable
- Starter guide

- User Software DVD-ROM
- · Warranty card
- · Telephone cable

